



PRESStige MGX - 1425 & 1426

3.5 MIL WHITE & CLEAR
GLASSMATE

1500 FENPARK DRIVE, FENTON, MO 63026 P: 636.349.6401 F: 636.349.6402 W: MGXDIGITAL.COM E: SALES@MGXDIGITAL.COM

Intended use:

On stationary glass and glossy plastic surfaces. Not recommended for exterior windows on moving vehicles.

Facestock	white or clear PVC
Facestock Thickness	3.5 mil +/- 5% (88 microns)
Release Liner	92 lb. Bleached Kraft (7.0 mils [175 microns] thick, +/- 10%), Polyethylene coated on two sides
Adhesive	Ultra low-tack, repositionable/removable
Adhesive Thickness	.0005-.00075 inches (12.5-18.75 microns)
Adhesion On Glass	3.0 oz/in width (modified for 24 hour dwell time) (ASTM D-903)
Dimensional Stability	MD shrinkage .03%, TD shrinkage .09% Tested after 24 hours at 160°F (71°C), adhered to glass plates
Service Temperature Range	-20°F to 175°F (-29°C to 80°C)
Minimum Application Temperature	50°F (10°C)
Expected Interior Life	5 years, when applied properly to a freshly washed glass surface
Expected Exterior Life	1-2 years, when applied properly to a freshly washed glass surface
Storage Stability	2 years when stored at 70°F (21°C) and 50% relative humidity

These specifications are the result of tests performed under laboratory conditions in a controlled environment. Since actual usage conditions can vary widely, we recommend that this material be thoroughly tested prior to purchase. We will be happy to furnish complimentary sample material for this purpose. As noted in the application instructions, optimal results are achieved when this product is applied to a freshly washed glass surface.

Product Performance and Suitability Disclaimer

All descriptive information, performance data, and recommendations for the use of Masterpiece Graphix (MGX) products shall be used as a guide only, and do not reflect the specification or specification range for any particular property of the product. Furnishing such information is merely an attempt to assist you after you have indicated your contemplated use and shall in no event constitute an MGX company warranty of any kind. All purchasers of MGX products shall be responsible for independently determining the suitability of the material for the purpose for which it is purchased. No distributor, salesman, or representative of MGX is authorized to give any warranty, guarantee, or make any representation in addition or contrary to the above.