



MGX-2710
.002 Clear Bopp/Removable/75#
13x19

1500 FENPARK DRIVE, FENTON, MO 63026 P: 636.349.6401 F: 636.349.6402 W: MGXDIGITAL.COM E: SALES@MGXDIGITAL.COM

Facestock: A 2.3 mil white bopp with a 50% gloss level. Outstanding whiteness and opacity. Topcoated for printability using standard print methods and thermal transfer (with resin ribbon only). This film has high machine direction stiffness and tensile strength for superior high speed label dispensing.

Type:	Film	Basis Weight:	N/A		Federal Regulation Approval	
Caliper:	2.30 mil	Tensile:	MD: 20000 lb/in	CD: 35000 lb/in	Heavy Metals:	Yes
Opacity:	89.0 %	Tear:	MD: N/A	CD: N/A	Toy Safety:	Yes
Brightness:	N/A	Elongation:	MD: N/A	CD: N/A	Indirect Food:	Yes
					Direct Food:	No

Adhesive: A specialty clear acrylic adhesive showing good initial removable tack with high shear and high removable adhesion. This adhesive has excellent clarity & minimum cold flow. Good removability on a wide range of substrates including corrugated and many plastic surfaces.

Coat Weight:	Standard	Federal Regulation Approval		Typical Adhesion Values	
Adhesive Type:	Removable Acrylic	Heavy Metals:	Yes	Stainless Steel:	
Shear:	110 minutes	Toy Safety:	Yes	180° Peel:	4.7 lb/in
Minimum Application Temperature:	40° F	Indirect Food:	Yes	Loop Tack:	1.70 lb/in□
Service Temperature:	-65° F to 150° F	Direct Food:	No	Glass:	
ACTS Approval:	Yes			180° Peel:	3.0 lb/in
				Polyethylene:	
				180° Peel:	1.4 lb/in
				Corrugated:	
				180° Peel:	3.2 lb/in
				Painted Metal:	
				180° Peel:	4.5 lb/in

Release Liner: A clay coated kraft liner which has been silicone coated one side to give a controlled release. It is designed to withstand all diecutting, margin punching, perforating, fanfolding and refolding processes. It is an excellent layflat liner.

Basis Weight:	69 lb/ream	Tensile:	MD: 51 lb/in	CD: N/A	
Caliper:	4.6 mil	Tear:	MD: N/A	CD: 100 grams	

Product Performance and Suitability Disclaimer

All descriptive information, performance data, and recommendations for the use of Masterpiece Graphix (MGX) products shall be used as a guide only, and do not reflect the specification or specification range for any particular property of the product. Furnishing such information is merely an attempt to assist you after you have indicated your contemplated use and shall in no event constitute an MGX company warranty of any kind. All purchasers of MGX products shall be responsible for independently determining the suitability of the material for the purpose for which it is purchased. No distributor, salesman, or representative of MGX is authorized to give any warranty, guarantee, or make any representation in addition or contrary to the above.