



# ENDURANCE MGX - 1780

.010 MIL ONYX WHITE  
DEAD OPAQUE STYRENE

1500 FENPARK DRIVE, FENTON, MO 63026 P: 636.349.6401 F: 636.349.6402 W: MGXDIGITAL.COM E: SALES@MGXDIGITAL.COM

• Typical uses include packaging and one-time use items, printed toys & games, POP displays, silk screen printing, ID cards, menus, window signs

• Excellent printability, matte surface finish

• High heat distortion temperature, good low temperature toughness

PROPERTIES	CAS NUMBER	AMOUNT	EINECS	SYM	R-PHRASES
Modified Polystyrene	MIXTURE	> 99.9% weight	NA	NA	NA
Styrene	100-42-5	< 0.1% weight	202-851-5	Xn	R20, R36/38, R10

OCCUPATIONAL EXPOSURE LIMITS					
Component	Limit	TWA	STEL/Peak	Ceiling	Notation
Modified Polystyrene	CPCHEM	Not Established	NA	NA	NA

PHYSICAL/CHEMICAL	
Appearance	Opaque
Odor	Odorless Pellets
pH	NA
Vapor Pressure	NA
Vapor Density (AIR=1)	NA
Boiling Point	NA
Solubility (in water)	Soluble in hydrocarbon solvents; insoluble in water
Percent Volatile	<0.1
Melting Point	77°C (170.6°F) - 110°C (230°F)
Specific Gravity	1.03
Evaporation Rate	0

## Product Performance and Suitability Disclaimer

All descriptive information, performance data, and recommendations for the use of Masterpiece Graphix (MGX) products shall be used as a guide only, and do not reflect the specification or specification range for any particular property of the product. Furnishing such information is merely an attempt to assist you after you have indicated your contemplated use and shall in no event constitute an MGX company warranty of any kind. All purchasers of MGX products shall be responsible for independently determining the suitability of the material for the purpose for which it is purchased. No distributor, salesman, or representative of MGX is authorized to give any warranty, guarantee, or make any representation in addition or contrary to the above.